



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

PRODUCT DATA SHEET

BENTONE GREASE 2_

PRODUCT CODE – SP BG2

DESCRIPTION: Bentone grease is smooth, homogeneous prepared from dispersion of thickener in highly refined petroleum oil and fortified with performance additives as per application requirement.

FEATURES:

- **High** dropping point and can withstand high temperature of ambient to +150⁰C however can tolerate high temperature of 200⁰C also at once through application points through centralized lubrication system.

- Meets IS:12970 specifications.

APPLICATIONS:

Bentone grease is recommended for lubrication of machine elements, plain bearings and antifriction bearings operating at high temperatures as described in its features.

TYPICAL CHARACTERISTICS

S.No.	Characteristics	Test Method	Data
1	Appearance	Visual	Smooth and homogeneous
2	Color	Visual	Brown/Grey/Black
3	Thickener	-	Non soap
2	NLGI Grade	-	2*
3	Penetration workedx60	ASTM D-217	275
4	Drop point deg, C	ASTM D 2265	> 300

* Can be made in NLGI -1,0 grades also

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.