

## C-TEC E 726

---

<b>Technical data (Typical)</b>	Appearance (Visual)	Clear Yellow viscous liquid
	Color (ASTM D 1500)	L 4.5
	SP. Gravity @ 29.5°C (ASTM D 1298)	0.96 to 0.98 g/cc
	Viscosity @ 100°C (ASTM D 445)	250 to 310 cSt
	TAN (ASTM D 974)	MAX. 25 mgKOH/g
	Solubility 10% in 150SN (Internal)	Bright & Clear

---

### Application

C-TEC E 726 is a very high molecular weight ester designed to impart lubricity in straight cutting oils and soluble oils.

C-TEC E 726 is thermally stable and has the potential of replacing Chlorine fully or partially. It can be effectively used in soluble oil systems by combining with small amounts of a base.

Soluble oils formulated with C-TEC E 726 will form stable emulsions.

Suggested Applications:

Soluble oils  
Rolling oils

---

### Handling

Please refer to the corresponding material safety data sheet for handling and blending precautions and maximum recommended temperatures.

---

Krystal Lubetech Pvt. Ltd.  
B-17, Greenwood City, Sector – 45,  
Gurgaon – 122 002, Haryana  
Ph: 0124 – 4564401, Fax: 0124 – 4564444,  
E-mail: info@krystallubes.com

