

Krystal Lubetech Pvt. Ltd. B-17, Greenwood City, Sector- 45, Gurgaon,

HARYANA -122002 (INDIA)

PRODUCT DATA SHEET

CONCRETE MOULD OIL PRODUCT CODE-SP CMO

DESCRIPTION: Concrete Mould oil is prepared from highly refined petroleum oils and fortified with performance additives to give it high thermal stability.

FEATURES AND BENEFITS:

It has a low viscosity to provide satisfactory performance as concrete mould release oil.

APPLICATIONS:

Concrete Mould Release Oil is recommended as mould release oil for concrete moulds.

TYPICAL CHARACTERISTICS

S No.	Characteristics	Test Method	Data
1	Appearance	Visual	Clear liquid
2	Kin. Viscosity @40 deg C, cSt	ASTM D-445	5.1
3	Pour Point, deg C	ASTM D-97	< 0
4	Flash point, deg C,	ASTM D-92	Above 120
5	Specific Gravity	ASTM D-1298	0.86
6	SAP Value	Inhome	8.0

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.