

HIPER GA 107

Type	PREMIUM EP PACKAGE FOR GREASES	
-------------	---------------------------------------	--

Technical data (Typical)	Appearance	Clear Yellow Liquid
	Color (ASTM D 1500)	L 3.0
	Specific Gravity@ 29.5 °C (ASTM D 7042)	1.030 g/cc
	Viscosity @40°C, cSt (ASTM D 7042)	65.560
	Cu.corrosion @ 120°C For 9 hrs. 3.5% in 500 N Grp II 3.5% in Bright stock (ASTM D 130 M)	1b 1b
	Four Ball Weld Load 1.0% in 500N Grp II, Kg. 3.5% in 500N Grp II, Kg. (ASTM D 2783)	200 400
	Solubility 5% in 500N Grp II. (Internal)	Bright & Clear

Application	<p>HIPER GA 107 is a specially designed EP additive package to be used in greases for premium performance.</p> <p>HIPER GA 107 exhibits excellent load bearing characteristics at varied dosages between 1.0- 4.0 % depending up on the weld load requirements.</p> <p>The additive is also designed to exhibit very low Cu. Corrosion particularly in Lithium complex greases.</p>
--------------------	---

Handling	<p>Please refer to the corresponding material safety data sheet for handling and blending precautions and maximum recommended temperatures</p>
-----------------	--
