



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

PRODUCT DATA SHEET

Light Liquid Paraffin

TYPICAL PARAMETER	LIGHT LIQUID PARAFFIN IP	LIGHT LIQUID PATRAFFIN BP	LIGHT LIQUID PARAFFIN USP/Eph
Saybolt colour	+ 30	+ 30	+ 30
Odour and Taste	Odourless & Tasteless	Odourless & Tasteless	Odourless & Tasteless
Dynamic Viscosity @ 20°C, mPa s	25 to 80	25 to 80	N.A.
Kinematic Viscosity@40°C	N.A	N.A	Not more than 33.5
Specific Gravity@25	0.820 to 0.880	0.810-0.875	0.818-0.880
Acidity / Alkalinity(Neutrality)	Compiles as per standard	Compiles as per standard	Compiles as per standard
Solid Paraffin	Compiles as per standard	Compiles as per standard	Compiles as per standard
Sulphur Compound	Compiles as per standard	N.A.	N.A.
Readily Carbonisable Substance	Compiles as per standard	Compiles as per standard	Compiles as per standard
Light absorption in the range 240 to 280 nm	<0.1	N.A.	N.A.
Polynuclear Aromatics Compound	N.A.	Compiles as per standard	Compiles as per standard

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.