



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Technical Data Sheet

Calcium Hydroxide

Sl. No.	Characteristics	Test Method	Control Limit
1.	Appearance	Visual	Off White Powder
2.	Calcium Hydroxide, Ca(OH) ₂	ASTM C-25	95 % Min.
3.	Iron Oxide, Fe ₂ O ₃	Internal	0.3 % Max.
4.	Aluminum Oxide, Al ₂ O ₃	Internal	0.2 % Max.
5.	Sulfur, s	Internal	0.16 % Max.
6.	Magnesium Oxide, MgO	Internal	0.7 % Max.
7.	Silicon Oxide, SiO ₂	Internal	0.5 % Max.
8.	Carbon Oxide, CO ₂	Internal	2 % Max.

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.

