



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

Hydraulic Oil 32

SPECIFICATION

S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	28.7-35.3
5.	K. Viscosity @ 100° C	D-445	cSt	To report
6.	Viscosity Index	D-2270	-	90 Min
7.	Flash Point COC	D-92	° C	200 Min
8.	Copper Strip Corrosion	D-130	-	1a Max
9.	Pour Point	D-97	° C	-12 Max



Hydraulic Oils 32 is NSF H1 registered with NSF Reg. No. – 143355

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

Hydraulic Oil 46

SPECIFICATION				
S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	41.5-50.6
5.	K. Viscosity @ 100° C	D-445	cSt	To report
6.	Viscosity Index	D-2270	-	90 Min
7.	Flash Point COC	D-92	° C	200 Min
8.	Copper Strip Corrosion	D-130	-	1a Max
9.	Pour Point	D-97	° C	-9 Max



Hydraulic Oils 46 is NSF H1 registered with NSF Reg. No. – 143356

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

Hydraulic Oil 68

SPECIFICATION

S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	61.2-74.8
5.	K. Viscosity @ 100° C	D-445	cSt	To report
6.	Viscosity Index	D-2270	-	90 Min
7.	Flash Point COC	D-92	° C	200 Min
8.	Copper Strip Corrosion	D-130	-	1a Max
9.	Pour Point	D-97	° C	-9 Max



Hydraulic Oils 68 is NSF H1 registered with NSF Reg. No. – 143357

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.