



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

80W90 API GL 4

SPECIFICATION

S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	To report
5.	K. Viscosity @ 100° C	D-445	cSt	13.5-15.5
6.	Viscosity Index	D-2270	-	100 Min
7.	Flash Point COC	D-92	° C	165 min
8.	Pour Point	D-97	° C	-9 max

Note: - The Oil meets API GL-4 level.

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

80W90 API GL 5

SPECIFICATION

S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	To report
5.	K. Viscosity @ 100° C	D-445	cSt	13.5-15.5
6.	Viscosity Index	D-2270	-	100 Min
7.	Flash Point COC	D-92	° C	165 min
8.	Pour Point	D-97	° C	-9 max

Note: - The Oil meets API GL-5 level.

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

Product Data Sheet

85W140 API GL 5

SPECIFICATION

S.NO.	CHARACTERISTICS	ASTM	UNIT	Control Limit
1.	Appearance		Visual	Clear & Bright
2.	Sp. Density at 29.5° C	D-1298	g/ml	To Report
3.	Colour	D-1500	Visual	Natural
4.	K. Viscosity @ 40° C	D-445	cSt	To report
5.	K. Viscosity @ 100° C	D-445	cSt	28-32
6.	Viscosity Index	D-2270	-	100 Min
7.	Flash Point COC	D-92	° C	165 min
8.	Pour Point	D-97	° C	-9 max

Note: - The Oil meets API GL-5 level.

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.