



# Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,  
HARYANA -122002 ( INDIA)

## Technical Data Sheet

### Name of the Product: SN-70 (Group II)

Sl. No.	Characteristics	Test Method	Control Limit
1.	Appearance	Visual	Clear & Bright
2.	Color	ASTM D-1500	0.5 Max.
3.	Specific Density @ 29.5 ° C, gm/ml	ASTM D-1298	To report
4.	Kinematic Viscosity @ 40 ° C, Cst	ASTM D-445	10-14
5.	Kinematic Viscosity @ 100 ° C, Cst	ASTM D-445	2.5-3.5
6.	Viscosity Index	ASTM D-2270	100 Min.
7.	Flash point COC ° C	ASTM D-92	160 Min.
8.	Pour Point ° C, Max	ASTM D-97	-6

**Technical Information:** Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.

