



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector- 45, Gurgaon,
HARYANA -122002 (INDIA)

PRODUCT DATA SHEET

SYNTHETIC INDUSTRIAL GEAR OILS 220/320/460/680

PRODUCT CODE –SPP SIGO

DESCRIPTION: Synthetic Industrial Gear Oils are formulated from synthetic hydrocarbon and fortified with performance additives to give it good antiwear and EP property.

FEATURES

- Excellent thermal stability, load carrying properties and corrosion protection.
- Low friction leading to lower energy consumption
- High viscosity index ensures reduced viscosity change with increase in temperatures.
- Good Demulsibility ensures total separation of water

APPLICATIONS:

Synthetic Industrial Gear Oils are recommended for lubrication of enclosed gear boxes and reduction units working at high temperatures and high load conditions.

TYPICAL CHARACTERISTICS

S No.	Test Description	Test Method	Data
1	VG Grade		220 320 460 680
2	Appearance	Visual	Clear liquid
3	Kin. Viscosity @40 deg C, cSt	ASTM D-445	223 325 462 688
4	Viscosity Index ,min.	ASTM D-2270	135
5	Flash point, deg C,	ASTM D-92	260
6	Copper corrosion, rating	ASTM D 130	1b

Technical Information: Technical information, recommendations, and other statements contained in this document or provided by Krystal Lubetech personnel are based on tests or experience that Krystal Lubetech believes are reliable, but the accuracy or completeness of such information is not guaranteed. Such information is intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Krystal Lubetech or third party intellectual property rights is granted or implied with this information.