



Krystal Lubetech Pvt. Ltd.

B-17, Greenwood City, Sector – 45,
Gurgaon – 122 002, Haryana

Ester T 163E

Description: Ester T 163E is a high viscosity pure trimer basestock containing branched chain alcohols which combines excellent high temperature oxidative stability with low volatility.

Application: Ester T 163E can be applied in the following: Gear Oils, High Temperature Grease, Conveyor Oven Chain Oils, and Automotive Engine Oils.

Benefits: Ester T 163E offers very good high temperature stability, low volatility, high viscosity and good lubricity.

Chemical and Physical Properties:

Property	Method	Specifications	Typical
Viscosity @ 100°C, cSt	ASTM D-445	15.9-16.7	16.3
Viscosity @ 40°C, cSt	ASTM D-445	198-227	213
Flash Point °C, C.O.C.	ASTM D-92	272 min	282
Pour Point, °C	ASTM D-97	-23 max	-29
Total Acid Number, mgKOH/g	ASTM D-664	0.05 max	0.01
Water Content, wt%	ASTM D-1533	0.05 max	0.02
Viscosity Index	ASTM D-2270		76
Appearance	Visual		Clear, Yellow Liquid
Hydroxyl, mgKOH/g	AOCS CD 13-60		1
Evaporation Loss, % 6.5 hrs @ 204C	ASTM D-972		3
Noack Evaporation Loss, % 1.0 hrs @ 250C	DIN 51-581		2
Specific Gravity 25/25C	ASTMD-4052		0.956
Density lb/gl @ 15.6 C	ASTM D-4052		8.04
Fire Point, C	ASTM D-92		310

Storage & Handling: Please see MSDS.

Packaging: Drums and bulk.

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.